

NO	Size	Resolution (R*G*B)	LCD Type	Disea P/N	Viewing Angle (O'clock)	luminance (cd/m2)	LED (PCS)	LCD Driver IC	Pin NO.	Module Interface	Touch Screen	Touch Driver IC	Outline Dimension(mm) W*H*D	AA Dimension(mm) W*H	Operating Temperature(°C)	Storage Temperature(°C)
1	1.3	240*240	Square Type	ZW-T013BQS-02	All	300	2P	ST7789V	24	8BIT MCU/4-SPI	NO	-	26.16*29.22*1.50	23.4*23.4	-20~+70	-30~+80
2	1.44	128*128	Square Type	ZW-T144HDS-01	6:00	200	1	ST7735S	22	8BIT MCU	NO	-	33.00*36.00*2.70	25.50*26.50	-20~+70	-30~+80
3	1.74	240*180	Transflective	ZW-T174YKH-01	8:00	150	3P	HX8347D	10	4-WIRE SPI	NO	-	40.77*36.20*2.40	35.28*26.46	-30~+70	-30~+80
4	1.77	128*160	TN	ZW-T177SSI-04	6:00	220	2P	ILI9163V	20	8BIT MCU	NO	-	34.70*46.70*2.60	28.03*35.04	-20~+70	-30~+80
5	1.77	160*128	Transflective	ZW-T177YTH-01	7:50	110	3P	HX8340B	30	8/16BIT MCU	NO	-	40.77*36.20*2.20	35.28*27.71	-20~+70	-30~+80
6	2.0	240*320	IPS	ZW-T020HQS-04	All	250	3P	ST7789V	45	MCU/RGB/SPI	NO	-	36.10*51.20*2.35	30.60*40.80	-20~+70	-30~+80
7	2.0	320*240	Transflective	ZW-T020LLI-01	All	150	3P	ILI9342C	40	RGB 6BIT+SPI	NO	-	46.10*40.96*2.40	40.80*30.60	-20~+70	-30~+80
8	2.1	480*480	Round Type	ZW-T021BCSA-01	All	250	4P	ST7701S	40	18BIT RGB	NO	-	56.18*59.71*2.20	φ53.28	-20~+70	-30~+80
9	2.3	480*360	IPS	ZW-T023BCSA-01	All	500	4P	ST7701S	27	1 LANE MIPI	NO	-	50.90*45.80*2.45	46.80*35.10	-30~+80	-30~+80
10	2.36	320*320	Round Type	ZW-T334TOS-01	12:00	650	5S	ST7796SI	17	1 LANE MIPI	NO	-	66.20*69.30*2.66	φ60.00	-20~+70	-30~+80
11	2.4	240*320	TN	ZW-T024SQH-05	6:00	280	4P	HX8347I	10	4-WIRE SPI	NO	-	42.72*60.26*2.34	36.72*48.96	-20~+70	-30~+80
12	2.4	240*320	IPS	ZW-T024HQL-25	All	500	2S3P	ILI9341V	40	MCU/RGB/SPI	NO	-	42.72*59.46*2.45	36.72*48.96	-20~+70	-30~+80
13	2.4	240*320	Transflective	ZW-T024YQSTR-01	2:00	200	4P	ST7789V	40	16BIT MCU	NO	-	42.72*60.26*2.37	36.72*48.96	-30~+75	-40~+80
14	2.7	960*240	TN	ZW-T027GOI-04	9:00	300	3S	ILI8691	40	8BIT RGB	NO	-	39.10*68.00*2.66	32.88*58.56	-20~+70	-30~+80
15	2.7	320*320	Square Type	ZW-T027BOIA-00	All	250	6P	ILI9488	40	18BIT RGB	NO	-	53.10*59.00*1.80	48.96*48.96	-20~+70	-30~+80
16	2.76	480*480	Round Type	ZW-T0276BCSA-01	All	250	4P	ST7701S	40	24BIT RGB	NO	-	73.03*76.48*2.26	φ70.13	-20~+70	-30~+80
17	2.8	240*320	TN	ZW-T028SQS-01	6:00	350	4P	ST7789V	50	MCU/RGB/SPI	NO	-	50.00*69.20*2.70	43.20*57.60	-20~+70	-30~+80
18	2.8	240*320	IPS	ZW-T028BQL-22	All	500	4P	ILI9341V	50	MCU/RGB/SPI	NO	-	50.00*69.20*2.35	43.20*57.60	-20~+70	-30~+80
19	3.1	480*800	IPS	ZW-T031BVS-01	All	450	6P	ST7701S	27	2 LANE MIPI	NO	-	43.68*77.02*1.65	40.32*67.20	-20~+70	-30~+80
20	3.5	240*320	IPS	ZW-T035BQSA-01	All	300	6P	ST7789V2	50	MCU/RGB/SPI	NO	-	54.5*83.00*2.10	51.27*68.36	-20~+70	-30~+80
21	3.5	240*320	Transflective	ZW-T035GQITR-01	6:00	100	6S	ILI9341V	50	18BIT RGB/SPI	NO	-	64.00*85.00*2.93	53.64*71.52	-20~+70	-30~+80
22	3.5	320*240	TN	ZW-T035GLH-01	12:00	350	6S	HX8238D	54	24BIT RGB	NO	-	76.90*64.00*3.05	70.08*52.56	-20~+70	-30~+80
23	3.5	240*320	TN	ZW-T035LLI-01	12:00	330	6S	ILI9488	50	MCU/RGB/SPI	NO	-	76.90*64.00*3.13	70.08*52.56	-20~+70	-30~+80
24	3.5	320*240	IPS	ZW-T035HLS-01	All	300	6S	ST7272A	54	24BIT RGB	NO	-	76.80*63.90*3.05	70.08*52.56	-20~+70	-30~+80
25	3.5	320*480	TN	ZW-T035SHI-11	6:00	330	6S	ILI9488	39	18BIT RGB	NO	-	54.48*84.71*2.15	48.96*73.44	-20~+70	-30~+80
26	3.5	320*480	IPS	ZW-T035BHSA-08	All	300	6P	ST7796U	50	24BIT RGB	NO	-	54.48*84.71*2.10	48.96*73.44	-20~+70	-30~+80
27	3.5	480*640	MVA	ZW-T035GCIA-01	All	180	6S	ILI9806E	40	18BIT RGB	NO	-	64.00*85.00*3.10	53.28*71.04	-20~+70	-30~+80
28	3.5	640*480	IPS	ZW-T035SGV-01	All	500	6S	NV3052C	40	24BIT RGB	NO	-	76.74*63.74*3.20	70.08*52.56	-20~+70	-30~+80
29	3.9	480*128	Bar Type	ZW-T039QPS-01	12:00	800	8S2P	ST7282	40	24BIT RGB	NO	-	105.50*37.00*3.05	95.04*25.344	-20~+70	-30~+80
30	4.0	480*480	Square Type	ZW-T040HCSA-03	All	400	4S2P	ST7701S	40	18BIT RGB	NO	-	74.83*78.98*2.02	71.86*70.18	-20~+70	-30~+80
31	4.0	720*720	Square Type	ZW-T395BMSA-01	All	500	4S2P	ST7703	30	4 LANE MIPI	NO	-	74.83*78.98*2.08	71.93*71.93	-20~+70	-30~+80
32	4.0	720*720	Round Type	ZW-T040BCSA-02	All	300	4S2P	SC7707	30	4 LANE MIPI	NO	-	105.61*109.87*2.09	φ101.52	-20~+70	-30~+80
33	4.0	400*960	Bar Type	ZW-T0399BUSA-01	All	450	8S	ST7701S	30	2 LANE MIPI	NO	-	42.90*102.08*2.15	39.18*94.03	-20~+70	-30~+80

NO	Size	Resolution (R*G*B)	LCD Type	Disea P/N	Viewing Angle (O'clock)	luminance (cd/m2)	LED (PCS)	LCD Driver IC	Pin NO.	Module Interface	Touch Screen	Touch Driver IC	Outline Dimension(mm) W*H*D	AA Dimension(mm) W*H	Operating Temperature(°C)	Storage Temperature(°C)
34	4.3	480*272	TN	ZW-T043QPH-108	12:00	850	9S	ILI6480B	40	24BIT RGB	NO	-	105.40*67.15*2.95	95.04*53.86	-20~+70	-30~+80
35	4.3	480*272	TN	ZW-T043QPH-108P	12:00	700	9S	ILI6480B	40	24BIT RGB	R-TP		105.40*67.15*4.15	95.04*53.86	-20~+70	-30~+80
36	4.3	480*272	TN	ZW-T043QPS-01	12:00	500	5S2P	ST7282	40	24BIT RGB	NO	-	105.50*67.20*3.00	95.04*53.86	-20~+70	-30~+80
37	4.3	480*272	TN	ZW-T043QPS-01P	12:00	420	5S2P	ST7282	40	24BIT RGB	R-TP	-	105.50*67.20*4.10	95.04*53.86	-20~+70	-30~+80
38	4.3	480*272	TN	ZW-T043QPS-01CP	12:00	420	5S2P	ST7282	40	24BIT RGB	C-TP	FT5436	105.50*67.20*4.75	95.04*53.86	-20~+70	-30~+80
39	4.3	480*272	TN	ZW-T043QPS-01P-B	12:00	420	5S2P	SSD1963	40	16BIT MCU	R-TP	-	105.50*67.20*5.20	95.04*53.86	-20~+70	-30~+80
40	4.3	480*272	IPS	ZW-T043BPIA-01	All	700	5S2P	ILI6485D	40	24BIT RGB	NO	-	105.50*67.20*2.95	95.04*53.86	-30~+80	-30~+80
41	4.3	480*272	IPS	ZW-T043BP5A-01	All	500	5S2P	ST7283	40	24BIT RGB	NO	-	105.50*67.20*2.95	95.04*53.86	-20~+70	-30~+80
42	4.3	480*272	IPS	ZW-T043BP5A-01CP	All	400	5S2P	ST7283	40	24BIT RGB	C-TP	FT5446-003	105.50*67.20*5.00	95.04*53.86	-20~+70	-30~+80
43	4.3	800*480	IPS	ZW-T043BWSA-04	All	300	4S3P	ST7262E43	40	24BIT RGB	NO	-	105.50*67.20*3.00	95.04*53.86	-20~+70	-30~+80
44	4.3	800*480	IPS	ZW-T043BWSA-06CP	All	400	5S2P	ST7262E43	40	24BIT RGB	C-TP	FT5446-003	105.50*67.20*4.75	95.04*53.86	-20~+70	-30~+80
45	4.6	800*320	Bar Type	ZW-T046QWI-01CP-Q	12:00	420	6S3P	ILI6137+ILI5960	40	24BIT RGB	C-TP	GT911	120.70*57.08*5.15	108.00*64.80	-20~+70	-30~+80
46	5.0	480*854	IPS	ZW-T495HVI-04	All	450	6S2P	ILI9806E	50	24BIT RGB	NO	-	66.30*120.30*2.51	61.63*109.65	-20~+70	-30~+80
47	5.0	480*272	TN	ZW-T050BPH-01	12:00	400	6S2P	HX8257	40	24BIT RGB	NO	-	120.70*75.80*3.10	110.88*62.83	-20~+70	-30~+80
48	5.0	480*272	TN	ZW-T050BPH-01P	12:00	300	6S2P	HX8257	40	24BIT RGB	R-TP	-	120.70*75.80*4.30	110.88*62.83	-20~+70	-30~+80
49	5.0	480*272	TN	ZW-T050BPS-01CP	12:00	350	6S2P	ST7257	40	24BIT RGB	C-TP	GT911	120.70*75.80*4.50	110.88*62.83	-20~+70	-30~+80
50	5.0	640*480	TN	ZW-T050QGH-24	12:00	300	5S3P	HX8292+HX8664	50	24BIT RGB	NO	-	111.55*87.86*5.70	101.57*76.18	-20~+70	-30~+80
51	5.0	800*480	TN	ZW-T050QWH-03	12:00	500	6S3P	ILI6122+ILI5960	40	24BIT RGB	NO	-	120.70*75.80*3.10	108.00*64.80	-20~+70	-30~+80
52	5.0	800*480	TN	ZW-T050QWH-03P	12:00	400	6S3P	ILI6122+ILI5960	40	24BIT RGB	R-TP	-	120.70*75.80*4.30	108.00*64.80	-20~+70	-30~+80
53	5.0	800*480	TN	ZW-T050QWH-51CP	12:00	420	6S3P	ILI6122+ILI5960	40	24BIT RGB	C-TP	FT5446-D03	120.70*75.80*5.28	108.00*64.80	-20~+70	-30~+80
54	5.0	800*480	IPS	ZW-T050BWSA-02	All	450	6S3P	ST7262	40	24BIT RGB	NO	-	120.70*75.80*2.85	108.00*64.80	-20~+70	-30~+80
55	5.0	800*480	IPS	ZW-T050BWSA-02P	All	350	6S3P	ST7262	40	24BIT RGB	NO	-	120.70*75.80*4.05	108.00*64.80	-20~+70	-30~+80
56	5.0	800*480	IPS	ZW-T050BWSA-02CP	All	400	6S3P	ST7262	40	24BIT RGB	CTP	FT5446-D03	120.70*75.80*5.03	108.00*64.80	-20~+70	-30~+80
57	5.5	720*1280	IPS	ZW-T055HMI-06	All	380	7S2P	ILI9881D	25	4 LANE MIPI	NO	-	71.44*129.90*1.81	68.04*120.96	-20~+70	-30~+80
58	5.5	1080*1920	IPS	ZW-T055BZIA-01	All	650	2S7P	ILI9885	31	4 LANE MIPI	NO	-	71.60*129.57*1.95	68.04*120.96	-20~+70	-30~+80
59	5.6	640*480	IPS	ZW-T0565BGEA-01	All	350	3S7P	JD9168S	40	18BIT RGB	NO	-	127.00*98.43*5.80	115.20*86.40	-20~+70	-30~+80
60	5.7	320*240	IPS	ZW-T057GLH-01	6:00	700	6S2P	HX8218A+HX8615A	54	24BIT RGB	NO	-	126.08*101.54*5.54	115.20*86.40	-20~+70	-30~+80
61	5.7	640*480	IPS	ZW-T057BGEA-01	All	650	3S7P	JD9168S	40	18BIT RGB	NO	-	127.00*98.43*5.80	115.20*86.40	-20~+70	-30~+80
62	7.0	280*1424	Bar Type	ZW-T070HURA-01	All	300	8S	OTA7290B	40	4 LANE MIPI	NO	-	38.20*181.47*3.4	33.60*170.88	-20~+70	-30~+80
63	7.0	800*480	TN	ZW-T070SWH-19	12:00	800	3S10P	HX8664B+HX8264E	50	24BIT RGB	NO	-	165.00*100.00*5.70	154.08*85.92	-20~+70	-30~+80
64	7.0	800*480	TN	ZW-T070SWH-19P	12:00	640	3S10P	HX8664B+HX8264E	50	24BIT RGB	R-TP	-	165.00*100.00*7.43	154.08*85.92	-20~+70	-30~+80
65	7.0	800*480	TN	ZW-T070SWH-99CP	12:00	700	3S10P	HX8664B+HX8264E	50	24BIT RGB	C-TP	FT5426-003	165.00*100.00*7.43	154.08*85.92	-20~+70	-30~+80

NO	Size	Resolution (R*G*B)	LCD Type	Disea P/N	Viewing Angle (O'clock)	luminance (cd/m2)	LED (PCS)	LCD Driver IC	Pin NO.	Module Interface	Touch Screen	Touch Driver IC	Outline Dimension(mm) W*H*D	AA Dimension(mm) W*H	Operating Temperature(°C)	Storage Temperature(°C)
66	7.0	800*480	TN	ZW-T070QWH-26	12:00	450	3S9P	HX8664B+HX8264E	50	24BIT RGB	NO	-	165.00*100.00*5.70	154.08*85.92	-35~+85	-35~+85
67	7.0	800*480	TN	ZW-T070QWH-26P	12:00	360	3S9P	HX8664B+HX8264E	50	24BIT RGB	R-TP	FT5426	165.00*100.00*6.85	154.08*85.92	-35~+85	-35~+85
68	7.0	800*480	TN	ZW-T070QWH-94CP	12:00	400	3S9P	HX8664B+HX8264E	50	24BIT RGB	C-TP	-	165.00*100.00*7.45	154.08*85.92	-35~+85	-35~+85
69	7.0	800*480	IPS	ZW-T070JWHA-11	All	500	3S8P	MOS_CHIP_G424A	40	24BIT RGB	NO	-	165.00*104.60*5.30	152.40*91.44	-30~+85	-40~+90
70	7.0	1024*600	IPS	ZW-T070BAHA-43	All	1000	3S10P	HX8282+HX8696	50	24BIT RGB	NO	-	164.80*99.80*5.60	154.21*85.92	-20~+70	-30~+80
71	7.0	1024*600	IPS	ZW-T070BAHA-09	All	500	3S10P	HX8282+HX8696	40	8BIT LVDS	NO	-	164.80*99.80*5.65	154.21*85.92	-20~+70	-30~+80
72	7.0	1024*600	IPS	ZW-T070BAHA-09P	All	400	3S10P	HX8282+HX8696	40	8BIT LVDS	NO	-	164.80*99.80*7.15	154.21*85.92	-20~+70	-30~+80
73	7.0	1024*600	IPS	ZW-T070BAHA-38CP	All	420	3S10P	HX8282+HX8696	40	8BIT LVDS	C-TP	FT5426	164.90*100.00*7.40	154.21*85.92	-20~+70	-30~+80
74	7.0	1024*600	IPS	ZW-T070BAHA-83CP-B	All	350	3S8P	HX8282+HX8696	19	HDMI	C-TP	ILI2511	165.30*121.00*7.42	154.21*85.92	-20~+70	-30~+80
75	7.0	1024*600	IPS	ZW-T070BAEA-04	All	400	3S9P	EK79007AD&EK73215BCGA	40	4 LANE MIPI	NO	-	164.90*100.00*2.92	154.21*85.92	-20~+70	-30~+80
76	7.0	1280*800	IPS	ZW-T070TIS-01	All	400	3S7P	ST5821C+ST5084C	40	8BIT LVDS	NO	-	161.00*107.00*3.35	149.76*93.60	-20~+70	-30~+80
77	8.0	800*600	IPS	ZW-T080QGI-01	12:00	350	3S9P	ILI6137+ILI5120U	50	24BIT RGB	NO	-	183.00*141.00*5.50	162.00*121.50	-20~+70	-30~+80
78	8.0	1024*768	IPS	DS-T080BXEA-01	All	300	3S11P	JD9165A	40	8BIT LVDS	NO	-	174.00*136.00*2.60	162.05*121.54	-20~+70	-30~+80
79	8.0	800*1280	IPS	ZW-T080BYE-02	All	250	4S6P	JD9366AB	40	4 LANE MIPI	NO	-	114.66*184.16*2.80	107.64*172.22	-20~+60	-30~+80
80	9.0	1024*600	TN	ZW-T090BAE-03	12:00	300	4S7P	EK79001HI/EK73215BCGA	60	8BIT LVDS	NO	-	211.10*126.50*3.4	196.61*114.15	-20~+70	-30~+80
81	10.1	1024*600	TN	ZW-T101BAH-09	12:00	380	3S13P	HX8282+HX8696	50	24BIT RGB	NO	-	235.00*143.00*5.10	222.72*125.28	-20~+70	-30~+80
82	10.1	1024*600	TN	ZW-T101BAH-09CP	12:00	320	3S13P	HX8282+HX8696	50	24BIT RGB	C-TP	GT928	235.00*143.00*7.25	222.72*125.28	-20~+70	-30~+80
83	10.1	1024*600	IPS	ZW-T101BAHA-01	All	500	3S13P	HX8282+HX8696	40	8BIT LVDS	NO	-	235.00*143.00*5.20	222.72*125.28	-20~+70	-30~+80
84	10.1	1024*600	IPS	ZW-T101BAHA-06	All	400	3S13P	HX8282+HX8696	50	24BIT RGB	NO	-	235.00*143.00*5.20	222.72*125.28	-20~+70	-30~+80
85	10.1	1280*800	IPS	ZW-T101BIHA-01	All	330	3S9P	TBD	40	8BIT LVDS	NO	-	229.56*149.16*2.67	216.96*135.60	-20~+70	-30~+80
86	10.1	1280*800	IPS	ZW-T101HIEWA-03	All	1000	7S6P	EK79202	40	8BIT LVDS	NO	-	229.46*149.10*4.80	216.96*135.60	-30~+85	-30~+85
87	10.1	1280*800	IPS	ZW-T101QIHA-39CP	All	350	3S14P	TBD	19	HDMI	C-TP	ILI2511	240.00*163.50*5.00	216.96*135.60	-20~+70	-30~+80
88	10.1	800*1280	IPS	ZW-T101BYIA-04	All	600	8S4P	ILI9881C	40	4 LANE MIPI	NO	-	143.00*228.60*2.60	135.36*216.58	-20~+70	-30~+80
89	10.1	800*1280	IPS	ZW-T101BYIA-04CP	All	500	8S4P	ILI9881C	40	4 LANE MIPI	C-TP	GT9271	163.60*245.50*4.55	135.36*216.58	-20~+70	-30~+80
90	10.1	1920*1200	IPS	ZW-T101BFH-01	All	300	6S6P	HX8290B	45	8BIT LVDS	NO	-	229.42*149.02*2.35	216.91*135.50	-20~+70	-30~+80
91	10.4	800*600	TN	ZW-T104TGH-02	12:00	350	3S12P	HX8282+HX9696	60	24BIT RGB	NO	-	228.50*175.50*6.00	211.20*158.40	-20~+70	-30~+80
92	15.6	1920*1080	IPS	ZW-T156BFH-01CP	All	400	10S6P	TBD	30	eDP	C-TP	2510	383.35*240.25*10.35	344.16*193.59	0~+50	-10~+60